

BenchRocker™ 3D

Benchmark Variable Speed Rocker



B3D2300

- + Multi-purpose - many applications
- + Three dimensional motion
- + Adjustable speed and tilt angle
- + Dual platform option expands workspace
- + Safe for incubator/cold room use

Technical Data

Speed:	Variable, 2 to 30 rpm
Tilt Angle:	Variable, 0 to 30°
Platform Size (3D):	30 x 30 cm / 12 x 12 in.
Load Capacity:	2.3 kg / 5 lb
Operating Temp. Range:	+4° C to +50° C
Dimensions (WxDxH):	30 x 30 x 20 cm 12 x 12 x 8 in.
Weight:	3.4 kg / 7.5 lb
Warranty:	2 Years
Electrical:	115V AC, 60 Hz, 0.3A 230V AC, 50 Hz, 0.15A

The BenchRocker 3D is designed to provide the precise speeds and tilt angles required for a broad range of molecular and biological mixing applications. The user can adjust both parameters to match the vessel size and the volume of liquid being mixed, yielding optimum results.

The rocking speed and tilt angle are both easily adjustable in seconds. At low speeds and minimal tilt angles the BenchRocker 3D provides a gentle wave effect for non-foaming mixing, as is required for most blot washing and gel work. When set to higher speeds and more extreme tilt angles it produces aggressive agitation for vigorous sample mixing.

The BenchRocker 3D can accept stackable platforms (clearance = 2.75 in.). All platform mats are autoclavable. It has a maintenance free brushless motor and is safe for use in cold rooms and incubators.

Ordering Information

B3D2300*	BenchRocker 3D variable speed rocker with dimpled and flat mats
BR1000-STACK	Optional stacking platform (12x12 in.) with flat mat
BR1000-STACK-D	Optional stacking platform (12x12 in.) with dimpled mat

*To order a product in 230V, please add -230 to item number.

Benchmark Scientific

VICTORY SCIENTIFIC